



Fresh air for your kitchen

The 6000 ExtractionTech Hood contains a powerful, efficient motor allowing you to clear your kitchen environment of fumes and cooking odours without waiting.

Product Benefits & Features

Clean air. Faster.

This Cooker hood clears the kitchen from cooking fumes quickly. That is because the advanced cooker hood has an efficient and powerful motor.

- Installation type: Chimney, width 80 cm
- Recirculatory intensive: 360 m³/h
- Power settings in recirculation mode (high/low): 350 / 230 m³/h
- Electronic touch controls on glass with speeds 3+Intensive
- Electronic Regulation
- Number of speeds: 3+Intensive
- Perimeter extraction for lower energy consumption and noise levels
- Light Temperature, K
- Watt Volt
- Grease filter type and number: Aluminium mesh, 1
- Indicator for grease filter saturation
- Indicator for carbon filter saturation
- Maximum noise level (high/low): 61/46 dB(A)

LEDlights for more refined cooking

Our LEDlights use far less energy than other lights, with a much longer life expectancy. And they provide expert illumination for greater detail while cooking.



Maximum filtration, again and again

A highly functioning filter that captures and removes fats and odours when cooking. The removable filter can be cleaned in the dishwasher, ensuring that your cooker hood is continually efficient.

Stylish glass touch-control panel for complete control

For complete control over the cooking process, this sophisticated glass panel provides precise one-touch control over vapour extraction.

Product Specification

Product Number Code	942 051 410	Sound power intensive, dB(A)	70
EAN	7332543792184	Sound power max speed, dB(A)	66
EPRELRegCode	454624	Sound power min speed, dB(A)	52
Annual Energy consumption, KWh/annum	53.3	Recirculation Intensive, m ³ /h	360
Energy Efficiency class	A	Recirculation Max, m ³ /h	350
Fluid dynamic efficiency class	A	Recirculation Min, m ³ /h	230
Fluid dynamic efficiency index	29.6	Recirc. sound power max, dB(A)	73
Lighting efficiency class	A	Recirc. sound power min, dB(A)	61
Lighting efficiency index	43.8	LightTemperature	3000
Grease filter efficiency class	E	Remote control	Not available
Grease filter efficiency index	55.1	Minimum distance from cooking top ELECTRIC	50
Height total	409	Minimum distance from cooking top GAS	60
Height max. external	409	Weight gross cleaner and accessories with packaging	18.93
Width mm	800	Weight net cleaner and accessories no packaging	15.3
Depth mm	152	Package heigth	530
Air outlet	150	Package width	920
Main colour	Black	Package depth	515
Charcoal filter type	ECFB02	Weight package Corrugated Cardboard	2600
Charcoal filter PNC	902 979 877	Weight package Paper/Carton	290
Voltage	230-240	Weight package Wood	0
Capacity intensive, m ³ /h	700	Weight package PE	650
Capacity, Max m ³ /h	570		
Capacity, Min m ³ /h	280		
Recirculation High	290		

