



The door to automatic drying

The dishwasher door is automatically opened at the end of the drying phase. Circulating air inside the machine to dry items naturally.

Product Benefits & Features



Powerful cleaning of the dirtiest loads

The Pro Intensiv program is specially designed to clean extremely dirty loads with the powerful action of hot water. Thanks to the 70°C water jet, which easily wipes out even deeply encrusted grime, it will get your dishes, pots and pans sparkling perfectly again.

- Water sensor detects the level of dirt and adjusts water consumption
- LED display
- AutoOff
- Warm water 60°C
- 4 programmes, 4 temperatures
- Dishwasher programmes: 30 MIN 60°, AutoSense 45°-70°, Eco, Intensive 70°
- Options: ExtraHygiene, XtraDry
- Delay start option from 1 to 24 hours
- Remaining time
- Inverter motor
- Height adjustable upper basket, even when fully loaded
- Upper basket with
- Cutlery basket
- Lower basket with Fixed plate racks
- AQUA-CONTROL
- Panel with symbols
- Indications for salt and rinse aid

Fast and efficient performance

This dishwasher gives you perfect performance - fast, thanks to its special half-hour program.



Ready when you are

Make the most of the time you have available with the delay start function in our dishwashers. Preset a start time, within a 3 hours time span after you have loaded your dishes, and enjoy the convenience of having clean dishes when you want them.

Product Specification

Product Number Code	911 514 004	Built in depth mm	0
Bar code	7332543531851	Built in height (min), mm	0
EnergyClassE20	F	Built in width mm	0
EnergyCons100CycleE20	104	Weight gross cleaner and accessories with packaging	43.15
RatedCapacityE20	13	Weight net cleaner and accessories no packaging	41.35
WaterConsE20	11	Package height	894
ProgrammeDurE20	3:47	Package width	635
NoiseClassE20	C	Package depth	680
NoisedBAE20	49		
OffModePwE20	0.5		
StandByPwE20	0.5		
DelayStartE20	4		
Installation in height	None		
Installation	FS		
Inlet hose type of	Aqua control		
Anti-flood device	Floating switch		
Water supply	Cold or hot		
Panel colour	White		
Required fuse (A)	10		
Connected load (W)	1950		
Voltage	220-240		
Cord length external	1.5		
Height total	850		
Width mm	600		
Depth mm	625		

PSGBDW210DE00005

