

**Keep your kitchen smelling fresh and clean**

Simply designed to suit any kitchen, this effective hood whips away cooking odours to keep your kitchen smelling fresh.

Product Benefits & Features**Set the speed quickly and easily**

The mechanical push-button controls on this cooker hood let you quickly and easily get more or less extraction speed and power as needed.

- Installation type: Chimney, width 90 cm
- Power settings in recirculation mode (high/low): 270 / 180 m³/h
- Number of speeds: 2
- Light Temperature, K
- Watt Volt
- Grease filter type and number: Aluminium Cassette, 3
- Maximum noise level (high/low): 65/46 dB(A)

Why spend more time cleaning appliances than you have to?

The aluminium cassette filter in this cooker hood is definitely low-maintenance. When it needs to be cleaned, simply pop it in the dishwasher!

Product Specification

Product Number Code	942 022 031	Sound power min speed, dB(A)	56
EAN	7332543610785	Recirculation Max, m ³ /h	270
EPRELRegCode	50404	Recirculation Min, m ³ /h	180
Annual Energy consumption, KWh/annum	63.9	Recirc. sound power max, dB(A)	66
Energy Efficiency class	D	Recirc. sound power min, dB(A)	59
Fluid dynamic efficiency class	E	LightTemperature	3000
Fluid dynamic efficiency index	8.1	Remote control	Not available
Lighting efficiency class	E	Minimum distance from cooking top ELECTRIC	50
Lighting efficiency index	8.25	Minimum distance from cooking top GAS	65
Grease filter efficiency class	C	Weight gross cleaner and accessories with packaging	15.6
Grease filter efficiency index	75.1	Weight net cleaner and accessories no packaging	13.3
Height total	678	Package height	625
Height max. external	1180	Package width	976
Width mm	898	Package depth	460
Depth mm	450	Weight package Corrugated Cardboard	2900
Air outlet	150	Weight package Paper/Carton	0
Main colour	Stainless Steel	Weight package Wood	0
Charcoal filter type	ECFB01	Weight package PE	60
Charcoal filter PNC	902 979 876	Weight package PP	0
Voltage	220-240	Weight package Polystyrene (EPS/EPP)	380
Capacity, Max m ³ /h	400		
Capacity, Min m ³ /h	240		
Recirculation High	220		
Sound power max speed, dB(A)	65		

